

What is claimed is:

1. A cable assembly comprising:
a cable including a plurality of lines each including a pair of signal conductors and a ground conductor;
a printed circuit board defining opposite top and bottom surfaces with a plurality of signal and ground conductive pads thereon, the signal conductors being fixed to the corresponding signal conductive pads, respectively;
a plurality of shielding metallic plates located between every adjacent two lines, respectively, for isolation, each of said shielding plates including at least one front finger located above the printed circuit board and fixed to the corresponding ground conductive pad on the printed circuit board, and a rear body portion extending rearwardly from the finger and behind the printed circuit board; wherein
each of said shielding plates is not fixed to any portions of the two neighboring lines except the ground conductor of only one of said two neighboring lines.
2. The assembly as defined in claim 1, wherein said signal conductive pads and said ground conductive pads are alternately arranged along one line on each of said top and bottom surfaces.
3. The assembly as defined in claim 2, wherein front end of the signal conductors of the lines and the front fingers of the shielding plates are aligned with one another in a lateral direction perpendicular to a front-to-back direction of the printed circuit board.
4. A cable assembly comprising:
a cable including a plurality of lines each including a pair of signal conductors and a ground conductor;

a spacer integrally connected to front portions of the lines to have said lines in an equidistant manner mutually;

a printed circuit board defining opposite top and bottom surfaces with a plurality of signal and ground conductive pads thereon, the signal conductors being fixed to the corresponding signal conductive pads, respectively;

a plurality of shielding metallic plates located between every adjacent two lines, respectively, for isolation, each of said shielding plates including at least one front finger located above the printed circuit board and fixed to the corresponding ground conductive pad on the printed circuit board, and a rear body portion extending rearwardly from the finger and behind the printed circuit board; wherein

the spacer is spatially located behind the printed circuit board, and each of said shielding plates is fully exposed outside of said spacer and mainly held by the printed circuit without involvement with said spacer.

5. The assembly as defined in claim 4, wherein said signal conductive pads and said ground conductive pads are alternately arranged along one line on each of said top and bottom surfaces.

6. The assembly as defined in claim 5, wherein front end of the signal conductors of the lines and the front fingers of the shielding plates are aligned with one another in a lateral direction perpendicular to a front-to-back direction of the printed circuit board.

7. A method of making a cable connector assembly, comprising steps of:
providing a cable with a plurality of lines each including a pair of signal conductors and a ground conductor;
providing a printed circuit board with opposite top and bottom surfaces having a plurality of signal and ground conductive pads thereon;

fixing the signal conductors to the corresponding signal conductive pads, respectively;

providing a plurality of shielding metallic plates between every adjacent two lines, respectively, for isolation, each of said shielding plates including at least one front finger located above the printed circuit board and, and a rear body portion extending rearwardly from the finger;

fixing the fingers to the ground conductive pads on the printed circuit board, respectively, and leaving the body portions disposed behind the printed circuit board; and

fixing the ground conductor of each of said lines to the corresponding shielding plate; wherein

each of said shielding plates is not fixed to any portions of the two neighboring lines except the ground conductor of only one of said two neighboring lines.

8. The assembly as defined in claim 7, wherein said signal conductive pads and said ground conductive pads are alternately arranged along one line on each of said top and bottom surfaces.

9. The assembly as defined in claim 8, wherein front end of the signal conductors of the lines and the front fingers of the shielding plates are aligned with one another in a lateral direction perpendicular to a front-to-back direction of the printed circuit board.